



# North Cool

PTAC SHEET

Date: February 22, 2008

MODEL			KCR-25C	KCR-32C	KCR-45C
<p>This design can be built with one of these 3 available configurations.</p>					
POWER SUPPLY		V/Hz/Ph	208-230/60/1	208-230/60/1	208-230/60/1
CAPACITY	COOLING	BTU/h	9000	12500	16000
		W	2700	3500	4500
	HEATING	BTU/h	9000	1200	15000
		W	2600	3300	4200
ELEC.HEATING			3000	3000	3000
POWER INPUT	COOLING	W	880	1140	1700
		HEATING	W	810	1060
ELEC.HEATER POWER INPUT		W	3020	3020	3020
OPERATING CURENT	COOLING	A	3.83	4.96	7.39
		HEATING	A	3,52	4.61
ELEC.HEATER CURRENT INPUT		A	13.13	13.13	13.13
EER	W/W		10.47	10.48	9.03
COP	W/W		10.95	10.62	8.43
AIR FLOW	INDOOR UNIT	m3/h	560	680	680
NOISE LEVEL	INDOOR UNIT	dB (A)	45-50	45-50	45-50
NET DIMENSION	WxHxD	mm	1066x555x408	1066x555x408	1066x555x408
PACKAGING DIMENSION	WxHxD	mm	1150x605x480	1150x605x480	1150x605x480
WEIGHT	NET	Kg	62	64	65
LOADING CAPACITY	40'HQ	Set	190	190	190